




- $\bullet \ \, {\it Truly compact and easy-to-use single-phase vacuum cleaner, ideal for ATEX environments.}$
- Single-phase brushless motor with a long lifespan for greater durability.
- Fully filtered air for cooling and motor exhaust.













INFO@COYNCO.COM WWW.COYNCO.COM

| TYPE | BSL |
|-----------------------------------|----------------------------|
| PRODUCT | BSL 100 BASIC ATEX 22 |
| VACUUMED MATERIAL | Dust |
| MOTORIZATION | Nr 1 By-pass Brushless |
| MARKING | 3D Ex h tc IIIB T 135°C Dc |
| ZONE | Zone 20/22 |
| POWER | 1400 W |
| VOLTAGE | 230 V |
| FREQUENCY | 50 Hz |
| AMPERAGE | 3,7 A |
| AIR FLOW | 240 m3/h |
| DEPRESSION | 360 mBar |
| DEPRESSION WITH VALVE | - |
| Ø SUCTION INLET | Type F Central - 50 mm |
| DIMENSIONS | 43x43 h50 cm |
| WEIGHT | 25 Kg |
| COLLECTION SYSTEM | Collection BAGS |
| DRUM-LONGOPACK INTERCHANGEABILITY | - |
| MATERIAL | - |
| FILTER CHAMBER DIAMETER | Ø 400 mm |
| FILTER TYPE | Cartridge |
| FILTER SURFACE | 2.600 cm2 |
| FILTER CLEANING | - |
| ABSOLUTE HEPA FILTER | - |



TYPE NO. MACHINES

вох

DIMENSIONS PACKAGE

WEIGHT