









INFO@COYNCO.COM
WWW.COYNCO.COM

- Single-phase or three-phase turbine for powerful suction capacity.
- \bullet Suitable for continuous 24/7 operation without maintenance, for long operational life
- Vacuum cleaner for dust and solids, ideal for general cleaning in industrial environments

| TYPE | PRO |
|---------------------------------------|--|
| PRODUCT | ST 3 |
| VACUUMED MATERIAL | Dust and liquids |
| MOTORIZATION | Turbine |
| POWER | 3 kW |
| VOLTAGE | 400 V 3P+E |
| FREQUENCY | 50 Hz |
| AMPS | 6,7 A |
| AIR FLOW | 320 m3/h |
| DEPRESSION | 320 mBar |
| VALVE DEPRESSION | 250 mBar |
| SUCTION INLET | Type B Tangential - 60mm |
| DIMENSIONS | 85x60 h135 cm |
| WEIGHT | 88 Kg |
| FILTER CHAMBER DIAMETER | Ø 460mm |
| TANK AND LONGOPACK INTERCHANGEABILITY | - |
| DISCHARGE SYSTEM | 50 Liters |
| FILTER TYPE | Cartridge - M Class Conductive alluminized |
| FILTERING SURFACE | 13.000 cm2 |
| FILTER CLEANING | Semi-automatic Pneu-mechanical Shaker |
| HEPA ABSOLUTE FILTER | Optional |

PACKAGING



| TYPE | NO. MACHINES |
|--------|--------------|
| вох | 1 |
| PALLET | 1 |
| PALLET | - |
| | |

| DIMENSIONS PACKAGE | |
|--------------------|--|
| 90X70 H150 CM | |
| 90X70 H190 CM | |
| - | |

WEIGHT
103 KG