



IPC

BY TENNANT COMPANY

VACUUM CLEANERS - INDUSTRIAL SOLUTIONS - OIL & SWarf

## GS 2/50 FM OPT OIL

Code: ASD013655

POWER MAX

2400 W

WATER LIFT

3700 mmH<sub>2</sub>O  
Flowmix ON

AIRFLOW

504 m<sup>3</sup>/h  
Flowmix OFF

TANK CAPACITY

50 l



FLOWMIX



DFS: DUAL  
FILTRATION  
SYSTEM

Industrial solution with easy to maneuver trolley and Flowmix system to collect heavier material

### EXCLUSIVE FEATURES

- ▶ ERGONOMIC INDUSTRIAL DESIGN WITH LIGHTWEIGHT MOTORHEAD
- ▶ BIG RUBBER WHEELS WITH BRAKES FOR EASY AND SAFE MANEUVERABILITY
- ▶ QUICK MAINTENANCE FRAMEWORK WITH DETACHABLE TANK
- ▶ SIEVE BASKET TO SEPARATE METAL SWarf FROM LUBRICATING LIQUIDS
- ▶ DFS - DUAL FILTRATION SYSTEM FOR SIMULTANEOUS WET & DRY PICK UP
- ▶ FLOWMIX SYSTEM TO REACH INCREASED VACUUM SUCTION
- ▶ INTEGRATED GASKET PROVIDES A HIGH QUALITY SEAL OF THE POWERHEAD
- ▶ VALVE FOR DRAINING LIQUID
- ▶ METAL TANGENTIAL INLET SEALED TO CREATE CYCLONIC EFFECT
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ EXTERNAL VISUAL FLUID INDICATOR FOR FILLING CONTROL



Suitable for suction of non-flammable liquids (oily emulsions) mixed with solid materials (metal shavings, swarf).

FRONT



SIDE



BACK



## SPECS



Solid structure with large wheels



FLOWMIX - to increase waterlift performance by 45%.



DFS: Dual Filtration System for simultaneous wet/dry pick up



Detachable tank



Sieve basket for solid/liquid separation



Visual fluid indicator

## TECHNICAL DATA

|                        |  | GS 2/50 FM OPT OIL                              |
|------------------------|--|---|
| Code                   |  | ASD013655                                       |
| PRODUCTIVITY           |  |   |
| Usage                  |  | WET&DRY   |
| Number of phases       |  | 1   |
| Voltage / frequency    |  | V / Hz 220-240 / 50-60                          |
| N. And type of motor   |  | 2   |
| Power                  |  | W 2000-2400 max                                 |
| Water lift             |  | mmH <sub>2</sub> O 2560 (FM OFF) / 3700 (FM ON) |
| Airflow                |  | m <sup>3</sup> /h 504 (FM OFF) / 173 (FM ON)    |
| Cable length           |  | m 8,5   |
| Filtering surface      |  | cm <sup>2</sup> 2360                            |
| Tank capacity/material |  | l 50 / Stainless Steel AISI 430                 |
| Sieve basket capacity  |  | l 30  |
| Sound pressure level   |  | dB(A) 74  |
| Diameter of inlet      |  | mm 60 - Metal, side entrance                    |
| Dimensions (LxWxH)     |  | mm 580x700x1150                                 |
| Weight                 |  | Kg 45   |

## STANDARD EQUIPMENT

Code: FTDP00285

**Washable polyester cartridge filter 2.360 cm<sup>2</sup>**



Code: FTDP28755

**Mesh filter**



Code: MPVR10591

**Internal ring**



Code: SECC00187

**Sieve basket 30 l**



## OPTIONAL ACCESSORIES

Code: PMDT01227

**Complete multipurpose premium tool kit 3 m Ø38 mm**

Code: PMDT01228

**Complete multipurpose premium tool kit 4 m Ø50 mm**

Code: PMDT00928

**Complete oil&abrasives tool kit 4 m Ø38 mm**

Code: PMDT00447

**Anti-oil tool kit for inlet Ø60 mm**