

Pipe cleaning hose 15 m G1/4 - PN450

414040

Pipe-cleaning hoses

Suitable for DYNAJET models up to 350 bar (5,075 PSI). Connect directly to the F 500 foot valve with the connecting nipple. Length: 15 m; connection: 1/4" ET / 1/4" ET

- F 500 foot valve for easy switching during pipe cleaning Art.No. [503865](#)
- Transition nipple for connection between foot valve and pipe cleaning hose Art.No. [427197](#)

Pipe cleaning nozzles for direct connection to pipe cleaning hoses

- Standard nozzle for universal use
for pipe diameter >30mm
as pulling nozzle for independent feed
 - DYNAJET 150me Art.No. [414046](#)
 - DYNAJET 280me + 350th Art.No. [434659](#)
 - DYNAJET 350th BP + 350me + 350mg + 350md Art. No. [414045](#)
- Rotating nozzles
for complete cleaning of all sides
for pipe diameter 30-100mm, not available as pulling nozzle
 - DYNAJET 280me + 350th Art.No. [434660](#)
 - DYNAJET 350th BP + 350me + 350mg + 350md Art.No. [414049](#)
 - 2 x 350me oder 2 x 350mg oder 2 x 350md Art.No. [459816](#)
- Poke nozzle
for cleaning of completely closed pipes, drilled as pulling nozzle for
pipe diameter >40mm
 - DYNAJET 150me Art.No. [414048](#)
 - DYNAJET 280me + 350th Art.No. [434661](#)
 - DYNAJET 350th BP + 350me + 350mg + 350md Art.No. [414047](#)



Base data

General technical data

Maximum pressure	350 bar (5,075 PSI)
Connection type (input)	1/4" ET
Connection type (output)	1/4" ET
Suited for hot water systems	Yes
Maximum temperature	Max. 100 °C
Weight (w/o fuel or water) in kg	4.1
Compatible with manufacturer	DYNAJET

Pipe and container cleaning

Application	Pipe cleaning
-------------	---------------

Aug 30, 2025