


K 1154-Series

NEW



CONVENIENT INTEGRATED HOSE REEL (TST)
space-saving storage of the high-pressure hose with twist stop screw connection

ACCESSORY STORAGE
neat storage for high pressure gun and lances

NON-SLIP RUBBER GRIP
for a secure hold

ROBUST CHASSIS
practically indestructible plastic housing

STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

OFF-ROAD CAPABILITY AND STABILITY
robust chassis for easy transport and high stability

WORKING POSITION

K 1154 TST | 602050

► **ACCESSORIES** | page 78-99



EQUIPMENT

- Quick release plug-in system D12
- Kränzle axial pump
- Total-Stop system
- Stepless pressure regulation
- High-pressure hose with Twist-Stop screw connection



VARIANT - NON-MARKING

NOM conversion kit Ord.no. 42251

For further information on NON-Marking please refer to page 79

MODEL	K 1154 TST	NEW
Ord.no. T5 without hose drum	602050	

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-140 3-14
Water output	l/min l/h	10 600
Admissible overpressure	bar MPa	160 16
Motor speed	Rpm	2800
Connection	V ~ Hz A	230 1 50 12.8
Power intake Power output	kW	2.95 2.2
Power supply cable	m	5
Plug		Schuko
Dimensions L x W x H	mm	470 360 875
Weight	kg	33

EQUIPMENT

High-pressure hose	m Ord.no.	15 (DN6) 48015
Trigger gun with safety catch	Model Ord.no.	Starlet 4 12525
Lance with flat jet nozzle	Nozzle Ord.no.	● 042 12435-M20042
Lance with Dirtkiller	Nozzle Ord.no.	● 042 12438-042

