

Roof cleaning system DRS-W 350 bar

426846

DYNAJET DRS-W roof-cleaning system

Suitable for corrugated roofs. Fully equipped with brush, manometer, 2/2-way ball valve for high-pressure on/off, wheels (distance adjustable), and nozzle bar for 2 identical shape D nozzles.

Connection: M22 x 1.5 ET.

Diameter: 400 mm

Nozzles, sealing and support ring to be ordered separately (not included).

Attention: two identical nozzles to be used

Choice of nozzles

Machine type	Dimensions	Shape	Art. No.
15° jet angle			
for 280me + 350th	0.95	D	498406
for 350me + 350mg + 350md	1.1	D	498401
30° jet angle			
for 280me + 350th	0.95	D	498393
for 350me + 350mg + 350md	1.1	D	498394
Sealing ring			484295
Support ring			489307

Rotating union Art.no. 418362

Splashguard roof cleaner Art.no. [549438](#)



Base data

General technical data

Maximum pressure	350 bar (5,075 PSI)
Connection type (input)	M22x1,5 ET
Maximum flow rate	30 l/min (7.94 USgal/min)
Suited for hot water systems	Yes
Maximum temperature	Max. 60 °C
Drive type	Self-driven
Outer diameter	400 mm
Dimensions (L/W/H)	680 x 520 x 420 mm

Weight (w/o fuel or water) in kg 17.42

Compatible with manufacturer Aquila, DYNAJET, Falch, Oertzen

Aug 30, 2025