

Roof cleaning system DRS 500 500 bar

546817

Ideal for cleaning concrete-tile und clay-tile roofs. Fully equipped with brush, manometer, 2/2-way ball valve for high-pressure on/off, wheels (distance and height adjustable to roof profile), and nozzle bar for 2 identical shape D nozzles.

Connection: M22 x 1.5 ET.

Diameter: 500 mm

Nozzles, sealing and support ring to be ordered separately (not included).

Attention: two identical nozzles to be used

Choice of nozzles

Machine type	Dimensions	Shape	Art. No.
15° jet angle			
for 280me + 350th	0.95	D	498406
for 350me + 350mg + 350md	1.1	D	498401
for 500me + 500mg + 500md	1.15	D	546669
for 500th + 500me-30	1.3	D	498402
30° jet angle			
for 280me + 350th	0.95	D	498393
for 350me + 350mg + 350md	1.1	D	498394
for 500th + 500me-30	1.3	D	447887
Sealing ring			484295
Support ring			489307

Rotating union Art.no. [546587](#)

Extension for roof cleaning system Art.no. [547985](#)



Base data

General technical data

Maximum pressure	500 bar (7,250 PSI)
Connection type (input)	M22x1,5 ET
Suited for hot water systems	Yes
Maximum temperature	Max. 100 °C
Outer diameter	500 mm
Dimensions (L/W/H)	702 x 530 x > 300 mm

Weight (w/o fuel or water) in kg 20.7

Compatible with manufacturer DYNAJET, Falch, Oertzen

Aug 27, 2025