A PURE WATER FILTERS

HYDRO POWER® ULTRA FILTER



THE HYDRO POWER® ULTRA SYSTEM

The Most Efficient DI Pure Water System Ever!

The **UNGER HydroPower®** Ultra is setting a new standard in deionising filter technology for pure water cleaning. A definite value-add for every professional glass and building cleaner.

Choose from 2 filter sizes. All 3 versions are supplied complete with **Ultra Resin Packs** and integrated **TDS meter** to monitor the outgoing water hardness.



DIUH1 HvdroPower® Ultra S



DIUH2 HvdroPower® Ultra L



DIUH3 HydroPower® Ultra LC

OVER 30 %* MORE PURE WATER PER RESIN FILLING

- Every Ultra resin pack contains a pre-portioned amount of UNGER premium ion-exchange resin with a new formula, perfected for glass cleaning
- The FloWater technology 2.0 in every Ultra resin pack ensures an efficient flow of water through the whole tank which optimises the resin saturation
- Intuitive colour coded system + KeyLock function eliminates risk of operating errors



FASTLOCK QUICK-FIT FASTENER

- Easy to open and close the tank
- Safe, self-locking mechanism with pressure-relief valve



TDS-METER

 Integrated digital measuring device displays the water hardness of the pure water coming out in ppm



ULTRA RESIN PACKS

• Can be changed as easily as a coffee pad in a coffee machine



HIGH-QUALITY METAL CONNECTIONS

- Stable quick-fit metal hose connector.
 Practical shut-off valve
- Reliable quick release connectors for hoses

FILTER OUTPUT

In particular the water hardness and the hydrogen carbonate content of the input water have a strong influence on the amount of pure water. The following values correspond to the output of **UNGER**HydroPower® Ultra with average tap water:



HydroPower Ultra S (DIUH1)				
Factor	Value			
Resin fill	1 × 6 l			
Pure water quantity per resin filling	710 l			
Working hours*	approx. 6 h			
Coverage in m ² **	approx. 600 m²			



HydroPower Ultra L (DIUH2)				
Factor	Value			
Resin fill	3 × 6 l			
Pure water quantity per resin filling	2.450 l			
Working hours*	approx. 20 h			
Coverage in m ² **	approx. 2.000 m ²			



HydroPower Ultra LC (DIUH3)					
Factor	Value				
Resin fill	3 × 6 l				
Pure water quantity per resin filling	2.450 l				
Working hours*	approx. 20 h				
Coverage in m² **	approx. 2.000 m²				

The pure water quantities (TDS < 10 ppm) were determined by an independent test laboratory at a water flow rate of 180 l/h and under the following conditions for the input water:

TDS: 275 ppm

Sum of cations and anions: 5,5 meq/l Hydrogen carbonate content of anions: 60%.

With *soft water* (<100 ppm) the pure water output can increase *more than 3 times*. With very hard water (>400 ppm), depending on the hydrogen carbonate content and ion concentration, the output can *decrease by more than half*.

- * at a water flow rate of 120 l/h
- ** with an area output of 100 m²/h

HydroPower® Ultra FILTER				
Part No.	Base	Height	Resin Packs	Cart
DIUH1	30 × 31 cm	35 cm	1 (6 เ)	-
DIUH2	30 × 31 cm	77 cm	3 (18 เ)	-
DIUH3	30 × 31 cm	107 cm	3 (18 l)	✓



CLEANING WITH THE HYDRO POWER ULTRA



PURE WATER FILTERS


ION EXCHANGE RESIN

RESIN CHANGE

The conductivity measurement is used to monitor water quality. If a conductivity measurement (integrated TDS-metre) indicates a value of > 10 ppm, the resin must be replaced.

Ultra RESIN PACKS FOR HYDRO POWER® ULTRA FILTER

Over 30 %* more pure water per resin filling



Ultra RESIN PACKS					
Part No.	Info	Pack			
DIUB1	3 × Ultra Resin Packs (18 l) for DIUH1, DIUK1	1			
DIUBS	1 × Ultra Resin Pack (6 l) for DIUH1, DIUK1	1			
DIUB3	Kit with 3 Ultra Resin Packs (18 l) for DIUH2, DIUH3	1			

Every Ultra resin pack contains a pre-portioned amount of UNGER premium ion-exchange resin with a new formula, perfected for glass cleaning

The FloWater technology 2.0 in every Ultra resin pack ensures an efficient flow of water through the whole tank which optimises the resin saturation





D١

JORO PON

QuickChange RESIN BAGS FOR HYDRO POWER® DI FILTER

High comfort



DIB64 DIB84 DIB84

4 bags (24 l) in air tight bag



融	DIB84		DIB64	
QuickChange RESIN BAGS 6 L				
Part No.	Info	Pack		
DIB64	4 bags (24 l) in air tight buck	et 1		

The QuickChange Resin Bags offer fast and easy resin replacement on the spot with minimal mess - anytime and anywhere!



PREMIUM GRADE VIRGIN MIXED BED RESIN

High capacity virgin mixed bed ion exchange resin for total de-ionisation and purification of water. Immediately produces 100 % pure water for streak free glass cleaning.





PREMIUM GRADE VIRGIN MIXED BED RESIN Part No. **Product** Pack DIP25 Bucket 25 l DIB25 Bag 25 l

Consisting of a mixture of a gel, type I strong basic anion exchanger, and a gel, strong acid-cation resin, for the direct demineralization of water. 40 % cation, 60 % anion, pH range 0-14.

Suitable for use in:

- Refillable DI cartridges
- DI pressure vessels
- Filters for Pure Water Window Cleaning

A PURE WATER FILTERS

HYDRO POWER® KITS







HydroPower® Ultra KITS	STARTER KIT POWER PAD	STARTER KIT ALU	STARTER KIT CARBON	EXPERT KIT L	EXPERT KIT LC
Part No.	DINK0	DIUK1	DINK1	DINK2	DINK3
HydroPower® Ultra Filter	DIUH1 (S)	DIUH1 (S)	DIUH1 (S)	DIUH2 (L)	DIUH3 (LC)
nLITE® Telescopic Pole	ED600 OptiLoc, 3 sections, 6m	AN60G Aluminium Master 6 m	CC60T Carbon Composite 6 m	CF86G Carbon 24K, 8,60 m	CF86G Carbon 24K, 8,60 m
nLITE® Angle adapter		NGC15 S (15 cm)	NGS15 S (15 cm)	NGS15 S (15 cm)	NGS30 M (42 cm)
nLITE® Brush	PWH35 PowerPad 35cm	NFF28 Power, 28 cm, flagged	NFK28 Power, cpl. 28 cm, flagged	NFK28 Power, cpl. 28 cm, flagged	NFR28 I Angle Brush, 28 cm, flagged
nLITE® Hose	DLS25 Duro Flex 25 m	DLS25 Duro Flex 25 m	DLS25 Duro Flex 25 m	DLS25 Duro Flex 25 m	DLS25 Duro Flex 25 m
Accessories	NLWVI: Water flow regulator 10790: 2x Hooks&Loops strips				
Pack	1	1	1	1	1

 Length
 Length
 Length
 Length
 Length

 6,00m/20ft
 6,00m/20ft
 8,60m/28ft
 8,60m/28ft









	V -		0 ,
HydroPower® RO KITS	RO S COMPLETE KIT CARBON 24K	RO M HIGH RISE KIT HiMod	RO M SKY RISE KIT Ultra HiMod
Part No.	RONK1	RONK2	RONK3
HydroPower® RO Filter	R020C (R0 S)	R035C (RO M)	R035C (R0 M)
nLITE® Telescopic Main Pole	CF86G Carbon 24K 8,60m	UC67G nLite Connect HiMod 6,60m	UH67G nLite Connect Ultra HiMod 6,60m
nLITE® Extension Pole	CE33G		4x UH35G nLite Connect Ultra HiMod 3,40m
Accessories	NLHCC Extensionadapter		
nLITE® Angle adapter	NGS30 (M) 42 cm	NGC30 (M) 42 cm	NGC30 (M) 42 cm
nLITE® Brush	NFK41 Power, 41 cm, flagged	NFK41 Power 41 cm, flagged	NUR41 Angle brush 41 cm, unflagged
nLITE® Hose	DLH25 Duro Flex High Performance 25 m	DLH25 Duro Flex High Performance 25 m	DLH25 Duro Flex High Performance 25 m
Pack	1	1	1

Length 11,90m/39ft Length 13,40m/44ft Length 20m/72ft



WHICH PURE WATER FILTER IS EXACTLY RIGHT FOR YOUR PURPOSES?

